

## Ockwells Demolition Safety Film

### Description

A Polyethylene safety backing tape, coated with a special acrylic-based pressure sensitive adhesive. It has high tack, high adhesion and excellent holding power.

No.	Measured Aspect	Unit	Specification Requirement
1	Backing Film		PE Film
2	Adhesive		Acrylic
3	Colour		Transparent Clear
4	Appearance		Coated with free pressure sensitive acrylic adhesive
5	Thickness	mm	0.08 ± 0.005
6	Width	mm	600 ± 1
7	Internal Diameter	mm	76 ± 0.5
8	Adhesive Strength	g/50mm	1200 ± 10%
9	Elongation	KN/m	≥ 1.0
10	Elongation at Break	%	≥ 300
11	Temperature Resistance		60°C, 160 hours - no residue glue remains on the surface of the protected products after removal
12	Length	m	100 ± 1

### Note

All technical data is based on average values. Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but they are not to be construed in any manner as warranties expressed or implied.

The user shall determine the suitability of the product for their intended use and the user assumes all risk and liability whatsoever in connection herewith.

Properties of the products are susceptible to change due to various influences such as composition and condition of the substrate, impurities in or on the substrate, temperature and humidity of storage and the surrounding environment during application.

#### NEWBURY

Unit 6, Transigo,  
Gables Way, Thatcham,  
Berkshire RG19 4ZA  
**T: 01635 876336**  
sales@ockwells.com

#### WARRINGTON

Unit 29, Melford Court,  
Woolston, Warrington,  
Cheshire WA1 4RZ  
**T: 01925 820003**  
sales.warrington@ockwells.com

#### GLASGOW

Unit 2, 45 Maclellan Street  
Kinning Parkway Estate,  
Glasgow G41 1RR  
**T: 0141 427 3366**  
sales.glasgow@ockwells.com

#### EAST LONDON

Unit E1, Thames View  
Business Centre, Fairview Ind  
Park, Rainham RM13 8BT  
**T: 020 7473 8770**  
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.



It is recommended that a trial is conducted to consider the type of material on which the product is used, the surface finish, the temperature and processing constraints, and the time and conditions for exterior use.

We cannot be responsible for the misuse of the product, nor for the consequences of their usage for non-recommended applications.

### Health & Safety Note

The range of products currently being supplied by ourselves include various materials, commonly known as plastic tapes and foams, which are generally coated on one or two sides with a range of pressure sensitive adhesives.

From current knowledge available the actual tapes and foams themselves are not known to emit, either by vaporisation or contact, any substances which fall under the Substances Hazardous to Health Regulations.

Although at the time of application some of the adhesives are known to contain certain solvents covered by these regulations, these substances are however extracted during the manufacturing process and therefore are not present in the finished product.

#### NEWBURY

Unit 6, Transigo,  
Gables Way, Thatcham,  
Berkshire RG19 4ZA  
**T: 01635 876336**  
[sales@ockwells.com](mailto:sales@ockwells.com)

#### WARRINGTON

Unit 29, Melford Court,  
Woolston, Warrington,  
Cheshire WA1 4RZ  
**T: 01925 820003**  
[sales.warrington@ockwells.com](mailto:sales.warrington@ockwells.com)

#### GLASGOW

Unit 2, 45 Maclellan Street  
Kinning Parkway Estate,  
Glasgow G41 1RR  
**T: 0141 427 3366**  
[sales.glasgow@ockwells.com](mailto:sales.glasgow@ockwells.com)

#### EAST LONDON

Unit E1, Thames View  
Business Centre, Fairview Ind  
Park, Rainham RM13 8BT  
**T: 020 7473 8770**  
[sales.rainham@ockwells.com](mailto:sales.rainham@ockwells.com)

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.