

Double Sided PVC Tape

Product Description

Double sided Blue stretchable LDPE carrier coated with clear permanent synthetic rubber-based adhesive on closed side and clear removable synthetic rubber-based adhesive on the open side, supplied with white silicone liners.

Applications

Temporary fastening, especially for non-slip mats or carpets.

Features & Benefits

Perm/Peel

Application Notes

Apply with a firm pressure to clean, non-porous surfaces. Test an inconspicuous area before use to determine suitability.

Technical Performance

Description	Units	Value	Test Method
Total thickness	mic	150	Digital calliper
180° Peel	N/cm	Open side 15 Closed side 2.7	AFERA 5004
Elongation at break	%	4	AFERA 5004
Tensile strength	N/cm	17	AFERA 5004
Static shear	hrs	Open side 300 Closed side 24	FTM 8su acciaio
Rolling ball	cm	Open side 3 Closed side 3.5	PSTC 6
Performance Temperature	°c	Min -10 max +50	-

Storage Details

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA
T: 01635 876336
sales@ockwells.com

WARRINGTON

Unit 29, Melford Court,
Woolston, Warrington,
Cheshire WA1 4RZ
T: 01925 820003
sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Maclellan Street
Kinning Parkway Estate,
Glasgow G41 1RR
T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.