

www.ockwells.com



Ockwells PVC Easi-Peel Flame Retardant Low Tack Tape

Properties	Unit	Value
Total thickness	mm	0.15±0.015
Backing Thickness	mm	0.135±0.013
Glue thickness	mm	0.015±0.015
Adhesive	-	Rubber
Elongation	%	≥ 130
Peel adhesion	N/cm	≥ 1.6
Tensile strength	N/cm	≥ 20
Flammability	-	Self-Extinguishing
Application	°C	0~50
temperature		
Heat resistance	°C/min	-12~80
Storage temperature	°C	Normal room temp.
Shelf life	Month	24

- 1. The data above is typical and subject to change without notice.
- 2. The product should be stored at room temperature and kept from moisture and heat source.
- 3. It is essential as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry and free of grease and oil.
- 4. Dimension Tolerance PVC Tapes:

Thick: ±0.015mm for thickness up to and including 0.20mm, ±0.03mm for greater thickness.

Width: ±1mm for widths up to and including 19mm, ±1.5mm for greater widths.

Length: ±30cm for lengths up to and including 25m, ±50cm for greater lengths within 100m.

NEWBURY

Unit 6, Transigo, Gables Way, Thatcham, Berkshire RG19 4ZA

T: 01635 876336

sales@ockwells.com

WARRINGTON

Unit 29, Melford Court, Woolston, Warrington, Cheshire WA1 4RZ T: 01925 820003

sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Maclellan Street Kinning Parkway Estate, Glasgow G41 1RR T: 0141 427 3366

sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770

sales.rainham@ockwells.com