

### Ockwells PVC Easi-Peel Low Tack Tape

Properties	Unit	Value
Total thickness	mm	0.15±0.015
Backing Thickness	mm	0.135±0.013
Glue thickness	mm	0.015±0.015
Adhesive	-	Rubber
Elongation	%	≥ 130
Peel adhesion	N/cm	≥ 1.6
Tensile strength	N/cm	≥ 20
Application temperature	°C	0 ~50
Heat resistance	°C/min	-12~80
Storage temperature	°C	Normal room temp.
Shelf life	Month	24

1. The data above is typical and subject to change without notice.
2. The product should be stored at room temperature and kept from moisture and heat source.
3. It is essential as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry and free of grease and oil.
4. Dimension Tolerance PVC Tapes:  
Thick: ±0.015mm for thickness up to and including 0.20mm, ±0.03mm for greater thickness.  
Width: ±1mm for widths up to and including 19mm, ±1.5mm for greater widths.  
Length: ±30cm for lengths up to and including 25m, ±50cm for greater lengths within 100m.

#### NEWBURY

Unit 6, Transigo,  
Gables Way, Thatcham,  
Berkshire RG19 4ZA  
**T: 01635 876336**  
sales@ockwells.com

#### WARRINGTON

Unit 29, Melford Court,  
Woolston, Warrington,  
Cheshire WA1 4RZ  
**T: 01925 820003**  
sales.warrington@ockwells.com

#### GLASGOW

Unit 2, 45 Maclellan Street  
Kinning Parkway Estate,  
Glasgow G41 1RR  
**T: 0141 427 3366**  
sales.glasgow@ockwells.com

#### EAST LONDON

Unit E1, Thames View  
Business Centre, Fairview Ind  
Park, Rainham RM13 8BT  
**T: 020 7473 8770**  
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.