

### Ockwells FR Door Sleeves

- Certified to LPS1207
- Protection against scratches, dust, dirt, paint etc
- Helps reduce the potential costs of damage

#### Description

Ockwells Door Sleeves is a flame retardant LPS1207 compliant film, designed to protect doors during the refurbishment process. Ockwells Door Sleeves can be simply and quickly applied to universal door fittings, and can be held in place with jointing tape, providing a flame retardant, waterproof barrier to suit a range of demanding environments. Ockwells Door Sleeves are designed to provide high quality protection against scratches, dust, dirt, paint and mortar splashes. The Door Sleeves can also reduce costly damage to pre-finished doors during the refurbishment process. Ockwells Door Sleeves are supplied on a roll containing 50 bags per reel (POR -Perforated on a Reel) or in a Handy Pack (20 per pack). Each sleeve is 1100mm x 2200mm allowing the sleeve to be fitted to most metric and imperial doors with ease.

#### Certification

Ockwells Flame Retardant Door Sleeves have accreditation to LPS 1207, certified by Loss Prevention Certification Board in compliance with Loss Prevention Standard (Certification number-521a/02). LPS 1207 is the performance standard for protective materials that are used internally whilst buildings undergo refurbishment or construction.

#### Installation

Ockwells Door Sleeves can be fitted to most metric and imperial doors with ease. Simply tear off a sleeve from the roll at the perforation mark, and using the open end, pull the sleeve over the door. At the hinge door end, thread one side of the film through and overlap the sleeve by at least 150mm; then seal the lap with jointing tape. Any surplus film can be folded over the top of the door and should be secured with jointing tape to ensure a snug fit. This will allow the door to remain in operation whilst preventing cosmetic damage.

The use of non-certificated LPS 1207 materials could result in the withdrawal of insurance cover in the event of fire.

#### NEWBURY

Unit 6, Transigo,  
Gables Way, Thatcham,  
Berkshire RG19 4ZA  
**T: 01635 876336**  
[sales@ockwells.com](mailto:sales@ockwells.com)

#### WARRINGTON

Unit 29, Melford Court,  
Woolston, Warrington,  
Cheshire WA1 4RZ  
**T: 01925 820003**  
[sales.warrington@ockwells.com](mailto:sales.warrington@ockwells.com)

#### GLASGOW

Unit 2, 45 Maclellan Street  
Kinning Parkway Estate,  
Glasgow G41 1RR  
**T: 0141 427 3366**  
[sales.glasgow@ockwells.com](mailto:sales.glasgow@ockwells.com)

#### EAST LONDON

Unit E1, Thames View  
Business Centre, Fairview Ind  
Park, Rainham RM13 8BT  
**T: 020 7473 8770**  
[sales.rainham@ockwells.com](mailto:sales.rainham@ockwells.com)

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.