



Ockwells FleeceShield Standard

Product type

FleeceShield Standard Multifunctional nonwoven with adhesive coating with OPTICOAT™

Characteristic Properties

Material Nonwoven synthetic fibres
Top side with PE sheet acting as barrier against liquids
Rear side with slip resistant coating OPTICOAT™

Colour White

Technical Properties

Thickness 2mm

Water vapour permeability

Water in permeability

Water absorption ability

Advantages

Protects floors, carpets, stairs, tiles, etc. (E.g. from mechanical damage or stains from spilled liquids).
Helps to prevent accidents (Rear side with active protection against slipping).
Can be used several times, quickly laid out (Cost saving).
Environment-friendly (Free of harmful substances, thermally disposable).

Important

FleeceShield Standard is not suitable for newly laid floors, porous stone floors and clay tiles.

Laying

With overlap of 10 cm

Function / Application

Safe and highly effective protection for floors and surfaces of all kinds, including; carpets, tiles, furniture, etc.

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA
T: 01635 876336
sales@ockwells.com

WARRINGTON

Unit 29, Melford Court,
Woolston, Warrington,
Cheshire WA1 4RZ
T: 01925 820003
sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Maclellan Street
Kinning Parkway Estate,
Glasgow G41 1RR
T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.