Ockwells FloorShield FR

Description:

FloorShield FR (Daltex Flame Retardant Spunbond)

Ockwells FloorShield FR is a nonwoven fabric thermally bonded using a diamond pattern with a 19% bond area. FloorShield FR is used in a variety of applications offering good strength and abrasion resistance properties.

Product Identification: Printed with Ockwells details

Certified to BRE/LPCB LPS 1207 as FloorShield FR: Issue 3 Cert. 726a-x1/01

Technical Details:

Product type: Nonwoven Polypropylene
Material: Mix of Copolymer Polypropylene types
Weight: approx. 10 kg per 100m2
Colour: Grey
Dimensions: 1 x 100 rolls

Measured Aspect	Test Method	Units	Measurement
Base Weight	NWSP 130.1	g/m2	100
MD Tensile Strength	NWSP 110.4	N	250
CD Tensile Strength	NWSP 110.4	N	180
Tear Strength	ASTM D1424-07a	N	10

The Technical data on this specification are merely indicative and are a reflection of the properties of Ockwells FloorShield Flame Retardant.

Because of further development of the raw material and the production process changes are possible we reserve the rights make changes to the product without notice.

The description of the technical data and the composition of the product are merely for your information. We accept no responsibility for the completeness of the data and do not accept any claims with regard to the properties described.

NEWBURY
Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA
T: 01635 876336
sales@ockwells.com

WARRINGTON
Unit 29, Melford Court,
Woolston, Warrington,
Cheshire WA1 4RZ
T: 01925 820003
sales.warrington@ockwells.com

GLASGOW
Unit 2, 45 Maclellan Street
Kinning Parkway Estate,
Glasgow G41 1RR
T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON
Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.

The environment in which the product is used may have a great effect on and may change these properties.

Before using this product, the purchaser and or user must determine the suitability of this product for its intended use. The purchaser and or user assume all risk and liability in connection with this product.

Issue 2

NEWBURY
Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA
T: 01635 876336
sales@ockwells.com

WARRINGTON
Unit 29, Melford Court,
Woolston, Warrington,
Cheshire WA1 4RZ
T: 01925 820003
sales.warrington@ockwells.com

GLASGOW
Unit 2, 45 Maclellan Street
Kinning Parkway Estate,
Glasgow G41 1RR
T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON
Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.