

## Ockwells Hazard Warning PVC Tape

### Description

Manufactured from a plasticised polyvinyl chloride film and coated with an aggressive pressure sensitive rubber based adhesive.

### Applications

- Hazard Tape should be used to highlight hazards in and around construction sites
- Used on scaffolding poles and as a warning tape around trenches etc

Properties	Unit	Value
Total thickness	µm	150 ± 10
Adhesive	-	Rubber
Elongation	%	85
Initial Tack (Ball Test)	Ball no	≥ 10
180° Peel Adhesion	N/IN	≥ 2.5
Tensile Strength	N/IN	≥ 35
Service temperature	°C	0 ~ +80
Storage temperature	°C	Normal room temp.
Shelf life	Month	24

Unless otherwise indicated the figures above are average values and should not be treated at face value for specification purposes.

Application surface should be clean, dry and free of grease, oil, moisture, dirt and other conditions.

#### NEWBURY

Unit 6, Transigo,  
Gables Way, Thatcham,  
Berkshire RG19 4ZA

**T: 01635 876336**

[sales@ockwells.com](mailto:sales@ockwells.com)

#### WARRINGTON

Unit 29, Melford Court,  
Woolston, Warrington,  
Cheshire WA1 4RZ

**T: 01925 820003**

[sales.warrington@ockwells.com](mailto:sales.warrington@ockwells.com)

#### GLASGOW

Unit 2, 45 Maclellan Street  
Kinning Parkway Estate,  
Glasgow G41 1RR

**T: 0141 427 3366**

[sales.glasgow@ockwells.com](mailto:sales.glasgow@ockwells.com)

#### EAST LONDON

Unit E1, Thames View  
Business Centre, Fairview Ind  
Park, Rainham RM13 8BT

**T: 020 7473 8770**

[sales.rainham@ockwells.com](mailto:sales.rainham@ockwells.com)

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.