



Ockwells Megafilm Floor Protection

Description

Ockwells Megafilm floor protection systems are a range of embossed and moulded flame retardant plastic sheets designed to suit both carpet & hard floor applications, including wooden, vinyl & stone flooring. Ockwells Megafilm offers complete protection during refurbishment and redecoration and is available in a range of grades including light and high-performance carpet protection and hard floor protection.

- Approved to LPS1207 - LPCB
- Anti-slip
- Tear and puncture resistant
- Contains dirt and spillages
- Cover large areas fast
- Save labour time and costs

Ockwells Megafilm is certified by the Loss Prevention Certification Board in compliance with Loss Prevention Standard LPS 1207 which requires that the following standards are met:

- Ignitability-Small and Large Tests (BS 476: Part 12:1991 and LPS: BS5852)
- Smoke Emissions Test (prEN 2824 and prEN 2825)
- Toxic Gas Emission Test (prEN 2824 and prEN 2826)
- Critical Oxygen Index (BS 2782: Part 1:Method 141: 1986)

Installation

Ockwells Megafilm Floor Protection is available in a manageable roll size allowing you to cover large areas fast. The ease of installation helps speed up the protection process, reducing the risk of damage to exposed finishes. Ockwells Megafilm Floor Protection is flexible and durable, ensuring an all-round easy to install protection system.

Preparation

To ensure the highest performance of the material, protection should be installed as soon as all surfaces to be covered are clean and are fully cured where necessary.

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA
T: 01635 876336
sales@ockwells.com

WARRINGTON

Unit 29, Melford Court,
Woolston, Warrington,
Cheshire WA1 4RZ
T: 01925 820003
sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Maclellan Street
Kinning Parkway Estate,
Glasgow G41 1RR
T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.



Laying

Material should be laid print side up, unless directed otherwise. All rolls are supplied with fitting instructions.

Cut and Fit

Unroll the material and cut to fit desired coverage area. For larger area applications where jointing is required allow an overlap of at least 50mm; any pyramids will interlock to provide a trip free joint when taped securely. Pull protection taut to ensure that the material lies flat. Smooth down all taped joints and perimeters by applying pressure along their length.

Tapes

For total protection, tape perimeter edge of Megafilm and overlay adjacent sheets by 50mm and seal with relevant Ockwells tape.

Further Information

Storage & Handling: The materials used in Ockwells Megafilm are chemically stable and inert and are free of both solvents and aggressive chemicals. They are also clean and safe to use and contain no volatiles to 'seep' out. Due to their robust nature, Ockwells Megafilm requires no special conditions for storage, transport, handling or usage.

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA
T: 01635 876336
sales@ockwells.com

WARRINGTON

Unit 29, Melford Court,
Woolston, Warrington,
Cheshire WA1 4RZ
T: 01925 820003
sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Maclellan Street
Kinning Parkway Estate,
Glasgow G41 1RR
T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.