



Ockwells TS63 Flame Retardant Hard Surface Protection Film

Description

Ockwells TS63 Flame Retardant Hard Surface Protection Film is a 50 micron polythene surface protection film coated with a low tack solvent acrylic adhesive system. This film is UV stable for up to 6 months.

Applications

This product can be used on mirror finished steels where bending or cutting is required, as well as to protect medium gloss paint finishes, most non-porous surfaces, hard lacquered finished timber and anodised aluminium laminates. We do not recommend that this product is used on any coated glass (such as Pilkington Suncool™ or other solar control products).

Technical Details

Total thickness: 0.049mm

Backing thickness: 0.045mm

Tensile strength: 7n/cm

Elongation: 150%

Steel adhesion: 150g/25mm

Colours: Blue 600mm and 100mm wide

Flame Retardant Hard Surface Protection Film can be left in place on internal glass/non-porous surfaces for up to 6 months. It can also be used externally on glass for up to 28 days. The product has been tested without adverse effect on these surfaces. However, due to varying conditions on site and when used in direct sunlight we highly recommend that these time frames are not exceeded. Regular checks should be carried out on the performance of the film to assess if it needs to be removed and replaced.

Ockwells Flame Retardant Hard Surface Protection Film is a certified product:

Ockwells Flame Retardant Hard Surface Protection Film has shown a fire performance which ensures that, when the temporary protective covering is used on floors during building construction or refurbishment, it complies with the stringent guidelines of Warrington Certifire Certification.

- Technical Specification - TS63 Approved Product
- Warrington Certifire Certification - Cert. No. CF 747
- Factory Production and controls certified under ISO 9001:2008

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA
T: 01635 876336
sales@ockwells.com

WARRINGTON

Unit 29, Melford Court,
Woolston, Warrington,
Cheshire WA1 4RZ
T: 01925 820003
sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Maclellan Street
Kinning Parkway Estate,
Glasgow G41 1RR
T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.



If this product is used to protect horizontal surfaces any liquid spillages should be removed immediately and the film should be replaced as this could cause a slip hazard.

This product has been certified as “low slip risk” in dry conditions on hard surfaces but users must satisfy themselves that the product is suitable for the intended purpose.

The company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Please check that you have the latest issue of the information sheet.

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA
T: 01635 876336
sales@ockwells.com

WARRINGTON

Unit 29, Melford Court,
Woolston, Warrington,
Cheshire WA1 4RZ
T: 01925 820003
sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Maclellan Street
Kinning Parkway Estate,
Glasgow G41 1RR
T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View
Business Centre, Fairview Ind
Park, Rainham RM13 8BT
T: 020 7473 8770
sales.rainham@ockwells.com

These properties are the Manufacturer's typical values based on the average of several tests. As the installation and handling of this product is beyond our control, the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Ockwells also holds the right to change specification data without prior notice.